

COLORBODY™ PORCELAIN

SEASON WOOD™



SEASON WOOD™

COLORBODY™ PORCELAIN



CREATE A TRULY UNIQUE RUSTIC WOOD LOOK WITH THE DURABILITY OF A PORCELAIN TILE

Solve the ultimate dilemma with this superbly detailed Colorbody Porcelain tile with a natural weathered wood design. Unlike hardwood, Season Wood by Daltile allows you to have the warm natural look of wood flooring in any space. Whether the project is commercial or residential, this high-end wood styling will provide long-lasting endurance where wood would not.

- **LARGE-FORMAT PLANKS**
 - Stylish large planks provide an opportunity for distinctive designs in both commercial and residential spaces
- **EASY INSTALLATION & MAINTENANCE**
 - Tru-Edge™ technology makes installation clean and easy, while the porcelain tile is easy to maintain
- **DISTINCTIVE VISUALS & NEUTRAL COLORS**
 - The color palette, along with two distinctive visuals, allows Season Wood to integrate into any look and application naturally

SEASON WOOD™

COLORBODY™ PORCELAIN

WEATHERED



ORCHARD GREY SW01

NATIVE



WINTER SPRUCE SW02



AUTUMN WOOD SW03



SNOW PINE SW05



REDWOOD GROVE SW04

SEASON WOOD™ COLORBODY™ PORCELAIN



SIZES

			SQ.FT. CARTON	PCS. PER CARTON
	24 x 48 Field Tile	(23-3/8" x 46-7/8") (59.44 cm x 119.30 cm)	15.50	2
	12 x 48 Field Tile	(11-5/8" x 46-7/8") (29.65 cm x 119.30 cm)	11.64	3
	8 x 48 Field Tile	(7-3/4" x 46-7/8") (19.71 cm x 119.30 cm)	7.74	3
	6 x 48 Field Tile	(5-3/4" x 46-7/8") (14.71 cm x 119.30 cm)	11.64	6

RESIDENTIAL USAGE

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C	EP	

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	LIGHT RESIDENTIAL	COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios	✓	✓	✓	✓	✓
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops	✓	✓	✓	✓	✓
Pool Decking					
Pool Linings	✓	✓	✓	✓	✓

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.



By their very design, DalTile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.

TRIM

TYPE	NUMBER	SIZE	PCS. PER CARTON
 Floor Bullnose	S-43C9	3 x 12	30
 Cove Base	P-36C9T	6 x 12	22
 Cove Base Corner	PC-36C9T	1 x 6	15

Floor bullnose, cove base, and cove base corner trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

SHADE VARIATION



INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
3/8"	1/8" (3/16" when rectangular sizes are used in a staggered brick-joint pattern. Overlap should not exceed 33%)

TEST RESULTS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 450 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Dynamic C.O.F.	A137.1	≥ 0.42

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™ please visit <http://daltile.com/information/DCOF>.

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Special consideration needs to be given when installing tiles 20" and larger. Please refer to www.daltile.com/LargeTiles for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at: <http://daltile.com/CommercialFactors>.



DESIGN WITH CONFIDENCE™

7834 C. F. Hawn Freeway | Dallas, Texas 75217 | 800.933.TILE
For more information about DalTile products and services, visit our website at DALTILE.COM.
© 2014 Dal-Tile Corporation (3/14)